b.) Amendment to the Claims

1. (Currently Amended) A retroreflective sheeting comprising a surface layer providing a light entering side and a retroreflective element layer, with at least one destructive layer provided between the surface and retroreflective element layers, said destructive layer being comprising an alicyclic polyolefin resin or alicyclic acrylic resin; wherein, resin, wherein

when the retroreflective sheeting has been applied to a substrate and is removed, peeling takes place at the interface of the destructive layer and the layer which is in intimate contact therewith and/or by destruction of the destructive layer.

- 2. (Currently Amended) A retroreflective sheeting according to Claim 1, comprising an adhesive layer on a side opposite to a to said light-entering side of the retroreflective sheeting.
- 3. (Currently Amended) A retroreflective sheeting comprising a surface layer, <u>a</u> retroreflective element layer and an adhesive layer, with at least one destructive layer provided between any two of these <u>layers wherein said layers</u>, <u>said</u> destructive layer <u>is being</u> an alicyclic polyolefin resin or alicyclic acrylic <u>resin</u>; wherein, resin, wherein

when the retroreflective sheeting has been applied to a substrate and is removed, peeling takes place at the interface of the destructive layer and the layer which is in intimate contact therewith and/or by destruction of the destructive layer.

4. (Currently Amended) A retroreflective sheeting according to <u>any</u> one of Claims 1 – 3, in which the destructive layer resin is selected from the group consisting of cyclopentane resins (formula 1a, 1b, or 1c), vinylcyclopentane resins (formula 2a), vinylcyclopentanorbornene resin (formula 2b), and cyclohexadiene resin (formula 3a) and cyclohexane resin (formula 3b):

$$\begin{array}{c|c}
\hline
\\
R^{1}
\end{array}$$
(1a)

$$\begin{array}{c|c}
\hline
 & CH_2^-CH_2^-\\
\hline
 & R^3
\end{array}$$
(2a)

$$\begin{array}{c|c}
\hline
 & CH_2^-CH_2^-\\
\hline
 & R^3
\end{array}$$
(2b)

$$\begin{array}{c|c}
\hline
\end{array}$$
(3a)

, wherein wherein R^1 is hydrogen or cyclohexyl group, and R^2 and R^3 are independently selected from the group consisting of hydrogen, methyl, cyano, methoxycarbonyl, ethoxycarbonyl, cyclohexyloxycabonyl and n-butoxylcarbonyl.

5. (Currently Amended) A retroreflective sheeting according to <u>any</u> one of Claims 1 – 3, in which the destructive layer resin is a methacrylic acid ester resin (formula 4)

$$\begin{array}{c|c}
 & CH_3 \\
\hline
 & CH_2 & \hline
 & \\
 & CH_2 & \hline
 & \\$$

Claims 6-7 Cancelled.

- 8. (Currently Amended) A retroreflective sheeting according to $\underline{\text{any}}$ one of Claims 1-3, in which the destructive layer resin is poly-1,3-cyclohexadiene resin or polycyclohexane resin.
- 9. (Previously Presented) A retroreflective sheeting according to Claim 4, in which the retroreflective sheeting comprises enclosed lens-type or encapsulated lens-type micro-glass beads.

- 10. (Previously Presented) A retroreflective sheeting according to Claim 9, wherein the destructive layer is installed between the micro-glass beads and specular reflective layer.
- 11. (Previously Presented) A retroreflective sheeting according to Claim 4, wherein the destructive layer has a peeling strength ranging from 0.1 to 15 N/25 mm.
- 12. (Previously Presented) A retroreflective sheeting according to Claim 11, wherein the destructive layer has a glass transition point (Tg) of 90 190°C.
- 13. (Previously Presented) A retroreflective sheeting according to Claim 12, wherein the destructive layer has a percent transmission of total light ranging from 75 to 99%.
- 14. (New) A retroreflective sheeting according to claim 1, wherein said destructive layer comprises said alicyclic acrylic resin.